

# WebSphere DataPower Type 7198 and 7199: Quick Start Guide

---



This document summarizes the installation steps and reviews the most common signs-of-health for IBM® WebSphere® DataPower® Type 7198 and 7199 appliances. See the *Installation and User's Guide* for complete installation instructions.

Before defining the base configuration, gather the following information:

- The IP addresses for the Ethernet interfaces for management access.
- The IP addresses for Ethernet interfaces for service access.
- The IP address of the default gateways (routers) that supports the subnets for the Ethernet interfaces.
- The IP addresses and ports for the Web Management and SSH services. The Web Management service is required to accept the license agreement.
- Optional: The IP address and port for Telnet service.

## Physically installing

Before installing the appliance in the rack, review the graphics of the front and back panels in the *Installation and User's Guide* to know where to connect each type of cable.

To install the appliance in the rack:

1. Carefully unpack the appliance, and locate all supplied power cords, the serial cables, and the rails.
2. Identify the rack location for installation, and ensure there is sufficient space for ventilation and maintenance.
3. Secure the mounting rails.
4. Install the appliance on the rails, and slide the appliance into place.
5. Use network cables to connect at least one management Ethernet to a switch on your network. Ethernet cables are not supplied.
6. Use the supplied power cords to connect both power supplies to power outlets.
7. Connect the supplied serial cable from a system running terminal emulation software to the console connector. Ensure the connection is 9600 baud 8N1 (8 bits per character, no parity, 1 stop-bit), and no flow control.
8. Press the power button.

The power LED is illuminated. The terminal displays `DP0S...` From the ASCII terminal or PC running the emulation software, the `Login:` prompt is visible.

## Configuring the appliance for access

To define the base configuration for the appliance:

1. At the `Login:` prompt, enter `admin`.
2. At the `Password:` prompt, enter `admin`. The script will prompt you later to change this password.
3. Review and accept operational modes for the appliance.
4. Change password:
  - a. At the `Please enter new password:` prompt, enter a new password.
  - b. At the `Please re-enter new password to confirm:` prompt, enter the new password again.

5. At the Do you want to run the Installation Wizard? prompt, enter y to start the installation wizard.
6. Follow the prompts to complete the base configuration.
7. Follow the prompts to accept the license agreement.

## Accepting the licence agreement

You need to accept the license agreement through the WebGUI. To bring up the WebGUI:

1. From a network-connected PC, open a web browser.
2. In the **Address Bar**, enter the IP address and port of the Web Management interface. For example, enter `https://10.10.13.35:9090` as the address. Use the secure HTTP protocol (https, not http).
3. At the login panel, provide login credentials for the admin account:
  - a. In the **User** field, enter admin.
  - b. In the **Password** field, enter the revised password for the admin account.
4. Click **Login**.
5. Accept the license agreement.

After accepting the license agreement, the appliance reloads the firmware. In a few minutes, you can log in again after the appliance restarts.

## Confirming operational states

Confirm the following operational states:

- The power LED is illuminated.
- The fault LED is not illuminated.

If these states do not match your appliance, see the *Installation and User's Guide* for troubleshooting information.

If you have concerns, contact IBM Support. Go to <http://www.ibm.com/software/integration/datapower/support>.

---

**First edition (September 2011)**

© Copyright IBM Corporation 2011.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

(1P) P/N: 97Y0542

